


Villa Outdoor Station OEU-201S-HMK-W



Overview

OEU-201S-HMK-W is one of the terminal equipment of the digital building intercom system, with video intercom, security alarm, video surveillance, to provide a safe and comfortable living environment for residents. It can be used in villa residential building system.

Features

- Front panel: Aluminum alloy
- Supports batch configuration
- Supports call and intercom with the connected indoor stations and APP.
- Supports monitoring functions, security alarm, tamper alarm
- Supports Wi-Fi
- Built-in IC card reader

Specifications

Model	OEU-2015-HMK-W
Hardware Specification	
Operation System	Linux
Supplement Light	IR light(Adaptive infrared compensation)
FOV	Horizontal:124.3° Vertical:67.5° Diagonal:147.2°
Power Consumption	<10W
Volume Adjustment	Adjustable
Audio Quality	Noise suppression, echo cancellation and AGC
Audio Input	1 built-in omnidirectional microphone
Audio Output	1 built-in speaker
Audio Compression Standard	PCM, G711, MP3
Audio Compression Bitrate	128Kbps
Protection Level	IP65 (Apply waterproof glue to the gap between the device and the wall. For more information, see the quick guide.) IK08
Power Supply	DC 12V±25% input;IEEE802.3af, Standard PoE
Weight	0.267Kg
Mount Method	Wall mounted, flush installation
Network	100Mbps network port, supports IEEE802.3af PoE power supply, WIFI
Interface	Power *1, network port *1, RS485, door lock interface *2, IO input *4
Resolution	2MP
Dimensions (L x W x H)	79mm×171mm×34mm
Operating Environment	-30°C~+60°C,10%~90%, non-condensing, outdoor
Operating Frequency	13.56MHz
Basic Business	
WDR	Support DWDR
Protocol	UNV private protocol
Button	1 physical button
Network protocol	TCP/IP, IPv4, HTTP, RTP, RTSP, NTP
Specification Index	
Card Capacity	10000
Linked Indoor Station Capacity	20
Compliance	
NDAA Compliant	Support

