

Superior SeismoProtect G3 Fibra

Wired seismic detector with an additional shock sensor

This is the device of the Superior product line. Only accredited Ajax Systems partners can sell, install, and administer Superior products.



3
GRADE
EN 50131

PD 6662
2017

INCERT


NFA2P

Built-in sensors for a wide range of threats

- | | | |
|--|--|---|
|  Piezoelectric sensor
Detects vibrations from drilling or cutting, explosions and physical force such as bending, pressing, or pushing. |  Accelerometer
Detects shocks and tilt angle changes. |  Digital temperature sensor
Detects rapid temperature rises and temperature threshold exceeding. |
|--|--|---|

Filtering false alarms

When the device detects vibration, the structure-borne sound is instantly processed by hardware and converted into a signal, which is analyzed and correlated by a software algorithm. This procedure helps promptly distinguish real threats from false alarms caused by a swinging door, repair or maintenance work nearby, and passing trains or large vehicles.



Installation at no extra cost


The detector comes with everything an installer might need to do the job without wasting time or money. Apart from the device itself, the complete set includes:

- Mounting plate for installing on curved metal or reinforced concrete.
- Armored cable to safeguard hub-to-detector connection.
- Additional self-test device to check the operational state of the piezoelectric sensor.
- A set of fasteners for different surface types and fixation methods.



Sabotage protection

- Tamper alarm: 2 tamperers
- Protection against short circuits and overvoltage
- Device authentication to prevent spoofing
- Detection of front lid integrity damage caused by drilling or cutting
- Temperature monitoring to detect attempts to cut the device (e.g., with an oxy-fuel welding equipment)
- Connection with armored cable to complicate cutting off the line



Fibra communication technology

- Wired connection range¹ between the detector and the hub at a distance of up to 2,000 m (6,550 ft)
- Encrypted communication
- Regular polling to display current device statuses
- One Fibra line combines dozens of various Ajax wired devices in any combination
- Connecting with 4-core signal or 8-core U/UTP twisted pair cables
- Support of additional modules that can split, extend, or power the Fibra line



Quick setup and easy maintenance

- No need to fully disassemble the device for mounting and wiring
- Pairing with the hub via the automatic line scanning or QR code
- On-site or remote configuration and testing via Ajax apps
- Automatic device self-diagnosis with status report
- Instant data-rich maintenance notifications

In an Ajax system, you can combine devices of all product categories: **Intrusion protection** (both Superior and Baseline), **Video surveillance**, **Fire and life safety**, or **Comfort and automation**. Create the system to suit your needs and manage it in a single interface.

Compliance EN 50131 (Grade 3) PD 6662:2017 INCERT NFA2P	Compatibility  For detailed information, scan the QR code or follow the link: ajax.systems/tools/devices-compatibility/?models=SP.G3.F-000-Y	Installation Operating temperature range from –25 °C to +70 °C from –13 °F to 158 °F Operating humidity up to 95%	Complete set Superior SeismoProtect G3 Fibra Mounting plate Self-test device Armored 4-core signal cable Installation kit Quick start guide
Communication with a hub Fibra communication technology Wired connection 4×2×0.51 U/UTP cat.5 cable with a copper conductor 4×0.22 signal cable with a copper conductor Communication range up to 2,000 m up to 6,550 ft With 4×2×0.51 U/UTP cat.5 cable Polling interval 12–300 s Adjusted by a PRO or user with admin rights in Ajax apps	Detection Sensitive elements 1 piezoelectric sensor 1 accelerometer 1 digital temperature sensor Operating radius 4 m (13.1 ft) concrete 2 m (6.5 ft) steel The operating radius may vary significantly depending on the structure integrity Sensitivity 3 levels Adjusted by a PRO or user with admin rights in Ajax apps Option to ignore single shock Adjusted by a PRO or user with admin rights in Ajax apps Tilt activation threshold from 5° to 25° Adjusted by a PRO or user with admin rights in Ajax apps Temperature sensor Alarms when the temperature increases by 5 °C (9 °F) within 5 s or exceeds +70 °C (158 °F)	Power supply Fibra line The hub powers the detector Operating voltage range 5–30 V ⁼⁼ Nominal operating voltage 24 V ⁼⁼ Quiescent current consumption at nominal voltage 0.3 mA Maximum current consumption at nominal voltage 12 mA	Enclosure Color black, white Material aluminum, polycarbonate Dimensions 88 × 88 × 20 mm 3.46" × 3.46" × 0.79" Detector weight 170 g 6 oz Mounting plate weight 224 g 7.9 oz Protection class IP43 Impact protection IK04

¹ When using a 4×2×0.51 U/UTP cat.5 cable.



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/superior-seismoprotect-g3-fibra

- ✉ support@ajax.systems
- 📌 @AjaxSystemsSupport_Bot
- 🌐 ajax.systems