



# EAGLE-2-BUL-FW

## 2MP HDCVI IR BULLET



### System Overview

Experience 1080P full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 1080P HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

### Functions

#### 4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio\*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the HCVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

\* Audio input is available for some models of HDCVI cameras.

#### Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 800m(1080P)/1200m(720P) transmission via coaxial cable, and up to 300m(1080P)/450m(720P) via UTP cable.\*

#### Simplicity

HDCVI technology inherits the born feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

#### Smart IR

The camera is designed with microcrystalline LED IR illumination for best lowlight performance. Smart IR is a technology to ensure brightness uniformity in B/W image under low illumination. The unique smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

- Max 30fps@1080P
- HD and SD output switchable
- 2.8mm fixed lens
- Max. IR length 40m, Smart IR
- IP67, DC12V



#### Multiple-formats

The camera supports multiple video formats including HDCVI, CVBS, and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820(UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

#### Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

#### Protection

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments. With working temperature range of -40 °C to +60 °C (-40 °F to +140 °F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

# EAGLE RANGE | EAGLE-2-BUL-FW

Technical Specification					Smart IR	Yes
Camera					Electronic Defog	Yes
Image Sensor					Mirror	Off/On
Effective Pixels					Privacy Masking	Off/On (8 area, rectangle)
Electronic Shutter Speed					Certifications	
PAL:1/25s~1/100000s NTSC:1/30s~1/100000s					Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Minimum Illumination					Port	
0.02Lux/F1.85, 30IRE, 0Lux IR on					Video Port	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
IR Distance					Power	
Distance up to 40 m (131.23 ft)					Power Supply	12V±30% DC
IR On/Off Control					Power Consumption	Max 3.3W (12V DC, IR on)
IR LEDs Number					Environment	
1					Operating Temperature	-40°C to +60°C (-40°F to +140°F); <95% (non-condensation)
Pan/Tilt/Rotation Range					Storage Temperature	-40°C to +60°C (-40°F to +140°F); <95% (non-condensation)
Pan: 0°~360° Tilt: 0°~180° Rotation: 0°~360°					Protection Grade	IP67
Lens					Structure	
Lens Type					Casing	Metal front face + plastic main body + metal bracket
Mount Type					Dimensions	240.7 mm × 90.7 mm × 90.4 mm (9.48" × 3.57" × 3.56")
Focal Length					Net Weight	410 g (0.90 lb)
Max. Aperture					Gross Weight	616 g (1.36 lb)
Angle of View					Dimensions (mm[inch])	
2.8 mm: 118° × 103° × 59° (diagonal × horizontal × vertical) 3.6 mm: 103.8° × 87.5° × 47° (diagonal × horizontal × vertical) 6 mm: 62.4° × 54.7° × 31.3° (diagonal × horizontal × vertical)						
Iris Type						
Min Photographic Distance						
DORI Distance	Lens	Detect	Observe	Recognize	Identify	
	2.8mm	37.3 m (122.37 ft)	14.9 m (48.88 ft)	7.5 m (24.60 ft)	3.7 m (12.13 ft)	
	3.6mm	53.3 m (174.86 ft)	21.3 m (69.88 ft)	10.7 m (35.10 ft)	5.3 m (17.38 ft)	
	6 mm	80 m (262.46 ft)	32 m (104.98 ft)	16 m (52.49 ft)	8 m (26.24 ft)	
Video						
Video Frame Rate						
CVI: 1080P@25fps/30fps; 720P@25fps/30fps; 720@50fps/60fps; AHD: 1080P@25fps/30fps; 720P@25fps/30fps; TVI: 1080P@25fps/30fps; 720P@25fps/30fps; 720@50fps/60fps; CVBS: 960H						
Resolution						
1080P (1920 × 1080); 720P (1280 × 720); 960H (960 × 576/960 × 480)						
Day/Night						
Auto switch by ICR						
BLC						
BLC/HLC/DWDR						
WDR						
DWDR						
White Balance						
Auto; manual						
Gain Control						
Auto; manual						
Noise Reduction						
2D NR						